

**TECHNICAL DATA SHEET**

**HP-2100**

**RE-DISPERSIBLE POLYMER POWDER**

**Product Description**

HP-2100 is a re-dispersible polymer powder based on a co-polymer of vinyl acetate and ethylene. The product is a free-flowing and white powder.

ITEM	SPECIFICATION	TEST METHOD
Solid content (105℃), %	≤98%	International method
Ash content (1000℃), %	14±2%	International method
Glass transition temperature ( ℃ )	-5 ℃	International method
Minimum film forming temperature	0~ 3 ℃	International method
PH value	5 ~ 8	International method

**Properties**

**Application**

HP-2100 is very good in flexibility and adhesion. It is specially suitable for tile grout, flexible exterior wall putty, repair mortar, EIFS mortar and etc.

**Package and storage**

Packed in paper-plastic bag lined with polyethylene bag, 25 KGS net each. It is recommended to be used within 6 months.

Storage under dry and clean condition in its original packaging and away from heat.

**Health and safety**

Please see separate Material Safety Data Sheet

Name: Re-dispersible polymer powder

CAS No.: 24937-78-8



Huzhou Mizuda Bioscience Co., Ltd.